

HITACK H

Product Description

High viscosity lubricating oil blended with selected EP additive for the purpose of reducing engine wear and extension of service life.

Benefits

- High load capacity.
- Engine wear prevention.
- Heat and friction force reduction between moving parts.
- High film strength.

Applications

- Appropriate for a slow moving heavy open gear with extreme pressure.
- Be able to lubricate bearings in sugar mill industry.
- Other Applications requiring high viscosity lubricant such as wire rope.

The Moving Innovation 

HITACK H

Typical Characteristics

Tests	Methods	Units	Results
			1150
Appearance			Black
Kinematic Viscosity at 100 °C	ASTM D 445	mm ² /s	1150
Flash Point (COC)	ASTM D 92	°C	260

Health and Safety

This product shows no significant health or safety hazard when used under the recommended applications and suitable handling.

Avoid the direct contact. Wash immediately after contact. Health and safety information is available on the Safety Data Sheet (SDS) which can be obtained from <http://pttlubricants.pttor.com>



Note: Data and information contained in this publication are based on standard test under laboratory conditions and/or performance test. To consider the use of PTT Lubricants' products in particular application, customer is responsible for determining whether product and information are appropriate for customer conditions or should consult with PTT Lubricants' technical service division. The procedure of using any lubricant may differ or change depended on different machines and their manuals. Therefore, we recommend to read, understand and review the latest SDS in order to ensure the use of product is accomplished safety.