

# DYNATRAC T300

SAE 40

## Product Description

DYNATRAC T300 is a high quality diesel engine oil developed to keep engine clean and reduce deposits for agricultural diesel engines. It helps to provide high wear protection and maintain engine performance.

## Benefits

- High performance of engine wear protection even in heavy duty condition.
- Provides superior engine cleanliness and prevent deposit accumulation.
- Prevents sludge formation as well as protect engine against rust and corrosion.
- Enhances engine efficiency and prolong oil drain intervals.

## Applications

- Designed for agricultural diesel engines such as pushcarts, power tillers and multi-purpose diesel engines.
- Recommended for multipurpose equipment such as water pumps.
- Suitable for diesel pick up trucks and commercial vehicles recommended monograde viscosity.

*The Moving Innovation* 

# DYNATRAC T300

SAE 40

## Typical Characteristics

Tests	Methods	Units	Results SAE 40
Density at 15 °C	ASTM D 4052	g/cm <sup>3</sup>	0.897
Kinematic Viscosity at 40 °C	ASTM D 445	mm <sup>2</sup> /s	146.4
Kinematic Viscosity at 100 °C	ASTM D 445	mm <sup>2</sup> /s	14.85
Viscosity Index	ASTM D 2270		101
Total Base Number	ASTM D 2896	mg KOH/g	11.1
Flash Point (COC)	ASTM D 92	°C	268
Pour Point	ASTM D 5950	°C	-21

## Performance Standards

- API CF, CF-2/SF
- ACEA E1
- CCMC D1/D2
- MB 227.0
- JAPANESE CD
- MIL-L-2104D
- ALLISON C-4
- CAT TO-2

## Health and Safety

This product shows no significant health or safety hazard when used under the recommended applications and suitable handling.

Avoid the direct contact. Wash immediately after contact. Health and safety information is available on the Safety Data Sheet (SDS) which can be obtained from <http://pttlubricants.pttor.com>



The product can cause some skin irritation and has flash point higher than 93.4°C

Note: Data and information contained in this publication are based on standard test under laboratory conditions and/or performance test. To consider the use of PTTOR Lubricants' products in particular application, customer is responsible for determining whether product and information are appropriate for customer conditions or should consult with PTTOR Lubricants' technical service division. The procedure of using any lubricant may differ or change depended on different machines and their manuals. Therefore, we recommend to read, understand and review the latest SDS in order to ensure the use of product is accomplished safety.

The Moving Innovation 