

RUBFLO 101L

Product Description

RUBFLO 101L is rubber process and extender oil, produced from high quality base oils. It is suitable for use in rubber production processes to improve rubber quality.

Benefits

- Good solubility, high flash point and low volatility
- High thermal and oxidation stability

Applications

- Suitable for use in rubber production process to improve a rubber quality.
- Suitable for use in production process which has mineral oil as one component of the product.
- Can be used as economical lubricating and once through oils.

The Moving Innovation



RUBFLO 101L

Typical Characteristics			
Tests	Methods	Units	Results
Density at 15 °C	ASTM D 4052-11	g/ml	0.9921
Kinematic Viscosity at 100 °C	ASTM D 445-11	mm²/s	8.694
Flash Point (COC)	ASTM D 92-16	°C	224
Pour Point	ASTM D 97	°C	18
Aniline Point	ASTM D 611-12	°C	37
Total Sulfur Content	ASTM D 4294	%wt.	4.59
Carbon Type Analysis			
%CA	ASTM D 2140-08	%	48
%CN	ASTM D 2140-08	%	29
%CP	ASTM D 2140-08	%	23

The above mentioned data are only indication and do not present any guarantee. Any deviations of the data are no reason for claim.

Health and Safety

This product shows no significant health or safety hazard when used under the recommended applications and suitable handling.

Avoid the direct contact. Wash immediately after contact. Health and safety information is available on the Safety Data Sheet (SDS) which can be obtained from http://pttlubricants.pttplc.com





Note: Data and information contained in this publication are based on standard test under laboratory conditions and/or performance test. To consider the use of PTT Lubricants' products in particular application, customer is responsible for determining whether product and information are appropriate for customer conditions or should consult with PTT Lubricants' technical service division. The procedure of using any lubricant may differ or change depended on different machines and their manuals. Therefore, we recommend to read, understand and review the latest SDS in order to ensure the use of product is accomplished safety.

