



SEATECH 5000

Diesel Engine Oil for Fishery

Product Descriptions

- **SEATECH 5000** : Multigrade, SAE 15W-40 and 20W-50, high quality diesel engine oils, developed for diesel engine in fishing vessels

Features/Benefits

- Provides best lubrication and prevents wear, corrosion, and rust
- Provides cleanliness with detergent additive added for better cleansing and soot-dispersing
- Enhances fuel economy and prolongs engine life
- Maintains viscosity, eliminates plugging in engine oil's path and filter throughout draining period

Applications

- Suitable for fishing vessels that use high speed diesel fuel under normal and severe conditions
- Well suitable for diesel engine which is recommended for a usage of high quality multigrade engine oil including heavy duty turbocharged engine
- Also well suitable for all small fishing vessels' engines

Remark : For PTT Seatech 5000 application, please consult the engine operation manual. In case of old engines with apparent engine oil consumption, SAE 20W-50 viscosity grade is recommended.

Performance Standards

- | | | |
|---------------|---------------|---------------|
| - API CF-4 | - ACEA E2 | - MB 228.1 |
| - MAN 271 | - MACK EO-K/2 | - JAPANESE CD |
| - ALLISON C-4 | | |

Key Properties

	SAE 15W-40	SAE 20W-50
- Viscosity @ 100 °C, cSt	14.6	18.8
- Viscosity Index	141	128
- Cold-cranking Simulator, cP	6,110 @ -20 °C	7,340 @ -15 °C
- Flash Point, (COC), °C	230	258
- Pour Point, °C	-27	-24
- Total Base Number, mg KOH/g	12	12

For more information, please contact Fuels & Lubricants Research Department, PTT Research & Technology Institute : Tel. (662) 537-3000 Ext. 2413, 3241
Fax. (662) 537- 3000 Ext. 2236, 3210 or Technical Service Division, Oil Business : Tel. (662) 537-2327-8, (662) 537-2408, (662) 537-2412.